Datasheet_FNC-0103FX(ST) _FNC-0104FX(ST)



one world_one brand_one level_

LevelOne Network Interface Cards

LevelOne Fast Ethernet 100Mbps Adapter with Fiber Connector



TECHNICAL DATA

Standard Conformance:

■ IEEE802.3, IEEE802.3u Fast Ethernet 100BaseFX

Data Transfer Mode/Speed

- PCI bus master
- Full or half-duplex mode
- 100Mbps

Network Interface:

- FNC-0103FX: ST multi-mode connector
- FNC-0104FX: SC multi-mode connector

Host Interface

32-bit 33/66Mhz PCI Rev.2.1

Cable Length

Half-duplex Class II Hub Node to Node 205 m Node to Hub 100 m Hub to Hub 5 m
Half-duplex Switching Hub Node to Node 412 m Node to Hub 412 m Hub to Hub 412 m Hub to Hub 412 m Hub Node to Node 2 km Node to Hub 2 km

Hub to Hub

 $2 \, \text{km}$

Chipset:

Intel

Diagnostic LEDs:

Link, FDX, Col, Activity

Physical Characteristics:

- Power Requirement: 2.0A at +5V
- Operating Temperature: 0°C to 50°C
- Operating Humidity: 5% to 90% RH
- Dimension: 130mm (W) x 80mm (H)
- Weight: 0.2kg

Emission:

- FCC Class B
- CE mark Class B

Driver Support

- Netware
- Windows for Workgroups, Microsoft LAN Manager
- Windows 95/98/NT /2000
- OS/2 warp, IBM LAN Server
- DEC Pathworks
- Banyan Vines
- Lantastic/Al
- SCO Unix

Ordering Information:

■ FNC-0103 FX (ST) Fast Ethernet Adapter with Fiber Connector

 FNC-0104FX (SC) Fast Ethernet Adapter with Fiber Connector

